

# A-Series AX-61 All-IP Platform with ASI streaming



**DVB-S2X** **DVB-GSE** **DVB-CID**



The A-Series is a next generation FPGA-based family of satellite modem, modulator and demodulator platforms. The AX-61 product line is based on a powerful architecture that supports the new DVB-S2X standard, providing users with a future-proof solution. Advanced features and benefits include higher modulation schemes up to 256APSK, a finer granularity of ModCods and advanced filtering.

Beyond DVB-S2X, the AX-61 platform can be extended to customized waveforms and user-defined data processing. Through an all-IP structure, the platform supports both native network operation as well as data streaming over IP. Built-in encapsulators and decapsulators provide support for the standard formats, such as GSE and MPE plus specialized

streaming like transparent baseband data, raw IQ information, space data formats and more.

A-Series devices are based on a new processing architecture that offers signal based advancements, a flexible software platform and improved access from monitoring and control to the transmission parameters. This allows direct real-time monitoring and quick adaptation to specific customer requirements. Scalable hardware ensures that operators can serve all applications from very low up to extremely high throughput.

The A-Series AX-61 devices feature ASI interfaces to support transport stream transmission as base function and provide license based IP functionality as extension.

## Key features

- DVB-S2X - ETSI EN 302 307-2
- DVB-S2 - ETSI EN 302 307-1
- DVB-S2X modulations:  
QPSK to 256APSK; normal, short, linear
- DVB-S2 modulations:  
QPSK to 32APSK; normal, short
- Symbol rates from 100 ksps to 75 Msps
- Data rate up to 360 Mbit/s integrated
- Roll-Off: 35 %, 25 %, 20 %, 15 %, 10 %, 5 %
- Low spurious output
- Transport Stream over ASI or IP
- Operates as Layer 3 Bridge or Layer 3 Router
- Predistortion ready for automatic group delay and nonlinearity compensation
- OptiACM controller (open for other ACM systems)
- Real-time M&C capabilities
- IP and baseband traffic shaping
- Generic Stream Encapsulation (GSE)
- Multiprotocol Encapsulation (MPE)
- CE compliant
- **3 years warranty**

# A-Series AX-61

## All-IP Platform with ASI streaming

Modulator Parameters:		AX-61 / AT-61	
<b>Signal Outputs:</b>		1x L-band output 950 ... 2150 MHz	
		1x IF output 50 ... 180 MHz (option IF)	
		<b>IF Output</b>	<b>L-band Output</b>
<b>IF-Output Frequency:</b>		50 ... 180 MHz	950 ... 2150 MHz
<b>Frequency Resolution:</b>		1 Hz	1 Hz
<b>Phase Noise:</b>			
10 Hz		-45	-45
100 Hz		-80	-75
1 kHz		-88	-88
10 kHz		-90	-90
100 kHz		-100	-100
1 MHz		-115	-115
max. values in dBc/Hz			
<b>IF-Output Characteristics:</b>		Impedance: 50 Ω or 75 Ω	Impedance: 50 Ω
		Return Loss: > 18 dB	Return Loss: > 18 dB
		Output Power: -25 dBm ... 5 dBm, 0.1 dB steps, ±0.5 dBm accuracy	Output Power: -30 dBm ... 0 dBm, 0.1 dB steps, ±0.5 dBm accuracy
		Output Power muted: < -85 dBm	Output Power muted: < -85 dBm
		Connector: BNC female	Connector: N female 50 Ω
			10 MHz reference output: 1.5 ±1.5 dBm (can be switched on/off)
<b>Spurious Outputs:</b>		Signal related: < -67 dBc, unmodulated carrier, 50 ... 90 MHz or 100 ... 180 MHz < -45 dBc, unmodulated carrier harmonics, out of band	Signal related: < -67 dBc, unmodulated carrier, 950 ... 1900 MHz < -55 dBc, unmodulated carrier, 1900 ... 2150 MHz < -45 dBc, unmodulated carrier harmonics, out of band
<b>Frequency and Clock Stability:</b>		Standard: ±2 x 10 <sup>-7</sup> (0 °C ... 50 °C, after warm up), aging: ±2 x 10 <sup>-8</sup> per day, ±1 x 10 <sup>-6</sup> per year	
		Option EXT: ±2 x 10 <sup>-8</sup> (-30 °C ... 60 °C, after warm up), aging: ±1 x 10 <sup>-9</sup> per day, ±1 x 10 <sup>-7</sup> per year	
<b>Symbol Rate:</b>		Max. Range: 100 ksps ... 75 Msps (depending on firmware option)	
		Step size: 1 sps	
<b>DVB-S2X Modulation / Coding:</b>		ModCods: (normal FEC frame)	QSPK 13/45, 9/20, 11/20 8PSK 23/36, 25/36, 13/18 16APSK 26/45, 3/5, 28/45, 23/36, 25/36, 13/18, 7/9, 77/90 32APSK 32/45, 11/15, 7/9 64APSK 11/15, 7/9, 4/5, 5/6 128APSK 3/4, 7/9 256APSK 32/45, 3/4
		ModCods: (short FEC frame)	QPSK 11/45, 4/15, 14/45, 7/15, 8/15, 32/45 8PSK 7/15, 8/15, 26/45, 32/45 16APSK 7/15, 8/15, 26/45, 3/5, 32/45 32APSK 2/3, 32/45
		ModCods linear: (normal FEC frame)	8PSK 5/9-L, 26/45-L 16APSK 1/2-L, 8/15-L, 5/9-L, 3/5-L, 2/3-L 32APSK 25/36-L 64APSK 32/45-L 256APSK 29/45-L, 2/3-L, 31/45-L, 11/15-L all according to ETSI EN 302307-2
<b>DVB-S2 Modulation / Coding:</b>		ModCods: (normal and short FEC frame; except 9/10 short FEC frame only)	QPSK 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32APSK 3/4, 4/5, 5/6, 8/9, 9/10
		Pilots Insertion: Physical Layer Scrambling:	on / off N = 0 ... 262141 all according to ETSI EN 302307-1
<b>Carrier ID:</b>		DVB-CID according to ETSI TS 103129	
<b>Signal Spectrum Mask:</b>		α = 0.35, 0.25, 0.20, 0.15, 0.10, 0.05 according ETSI EN 302307	

Specifications continued next page

# A-Series AX-61

## All-IP Platform with ASI streaming

Demodulator Parameters:	AX-61 / AR-61	
Signal Inputs:	1x L-band input 1x IF input	950 ... 2150 MHz 50 ... 180 MHz (option IF)
	<b>IF Input</b>	<b>L-band Input</b>
IF-Input Frequency:	50 ... 180 MHz	950 ... 2150 MHz
IF-Input Characteristics:	Impedance: 50 Ω / 75 Ω switchable Return Loss: >18 dB Input Power: -60 dBm ... -15 dBm (total aggregate power) IF-Connector: BNC female 50 Ω	Impedance: 75 Ω Return Loss: >13 dB Input Power: -70 dBm ... -20 dBm (total aggregate power) IF-Connector: F female LNB DC-Feed: 13.5V or 18 V (450mA) switchable, 22 kHz tone on/off, DISEqC 1.1 short circuit protected
Symbol Rate:	Max. Range: Step size:	100 ksps ... 75 Msps 1 sps
DVB-S2X Demodulation / Decoding:	ModCods non-linear: (normal FEC frame)	QPSK 13/45, 9/20, 11/20 8PSK 23/36, 25/36, 13/18 16APSK 26/45, 3/5, 28/45, 23/36, 25/36, 13/18, 7/9, 77/90 32APSK 32/45, 11/15, 7/9 64APSK 11/15, 7/9, 4/5, 5/6 128APSK 3/4, 7/9 256APSK 32/45, 3/4
	ModCods non-linear: (short FEC frame)	QPSK 11/45, 4/15, 14/45, 7/15, 8/15, 32/45 8PSK 7/15, 8/15, 26/45, 32/45 16APSK 7/15, 8/15, 26/45, 3/5, 32/45 32APSK 2/3, 32/45
	ModCods linear: (normal FEC frame)	8PSK 5/9-L, 26/45-L 16APSK 1/2-L, 8/15-L, 5/9-L, 3/5-L, 2/3-L 32APSK 25/36-L 64APSK 32/45-L 256APSK 29/45, 2/3, 31/45, 11/15 all according to ETSI EN 302307-2
DVB-S2 Demodulation / Decoding:	ModCods: (normal and short FEC frame; except 9/10 short FEC frame only)	QPSK 1/4, 1/3, 2/5, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 32APSK 3/4, 4/5, 5/6, 8/9, 9/10
	Demodulator auto detection: Physical Layer Scrambling:	Modulation- and FEC-type, pilots on/off are automatically detected N = 0 ... 262141 all according to ETSI EN 302307-1
Signal Spectrum Mask:	$\alpha = 0.35, 0.25, 0.20, 0.15, 0.10, 0.05$ according ETSI EN 302307-2	
Common Parameters:	AX-61 / AT-61 / AR-61	
Data Interfaces:	2x Ethernet RJ-45, 10/100/1000 Mbps auto sensing arbitrarily assignable for M&C and/or traffic operation	
Network Operation:	Layer 3 Bridge or Router for IPv4 packet transmission, IPv6 on request 256 IP/subnet routes towards satellite 64 baseband channels with independent DVB-S2X and encapsulation settings	
Data Encapsulation:	Generic Stream Encapsulation (GSE) according to ETSI TS 102606 Multiprotocol Encapsulation (MPE) according to ETSI EN 301192	
IP Data Rate:	up to 360 Mbps or 80000 pps rx+tx processing, subject to prevailing modem limits data rates/packet rates can vary in combination with complex internal processing (i.e. traffic shaping)	
Traffic Shaper/QoS on BB level:	configurable baseband channel limits based on symbol rate guaranteed and limited bandwidth individually configurable	
Traffic Shaper/QoS on IP level:	(contact factory for options)	
Transport Stream Input:	1x RTP/UDP IP over Ethernet according to IETF RFC 2250 2x ASI BNC female 75 Ω, input auto-redundant or manually selectable	
Transport Stream Output:	1x RTP/UDP IP over Ethernet according to IETF RFC 2250 1x ISI selectable from multistream carrier; null packet reinsertion 2x ASI BNC female 75 Ω, identical output	
OptiACM:	CCM / VCM / ACM functionality for point-to-point and point-to-multipoint links 64 ACM channels with separate MODCOD range and Es/N0 sensitivity (contact factory for options)	
Predistortion:	(contact factory for options)	
Monitoring and Control:	Protocol: SNMP Connection: UDP/IP over Ethernet/RJ-45 or in-band via satellite link	
	Protocol: HTTP (web browser interface) Connection: TCP/IP over Ethernet/RJ-45 or in-band via satellite link	
Internal Fan	FAN included	
Temperature Range:	0 °C ... 50 °C operating or -30 °C ... 60 °C operating (option EXT) -30 °C ... 80 °C storage	
Relative Humidity:	< 95 % non condensing	
User Interface:	LCD-Display 2 x 40 characters, 4 cursor keys, 2/4 function keys VFD-Display 2 x 40 characters, 4 cursor keys, 2/4 function keys (option EXT)	
Mains Power Input:	100 ... 240 V AC nominal, 90 ... 264 V AC max, 50 ... 60 Hz	
Mains Power Consumption:	Typ.: 65 VA / 45 W	
Mains Power Input Connector:	IEC C14	
Mains Fuse:	2 x 3.15 A time-lag fuse	
Dimension and Weight:	483 x 44 x 505 mm <sup>3</sup> (WxHxD), 1 RU (19") up to approx. 10 kg depending on device type	

Specifications are subject to change

# A-Series AX-61

## All-IP Platform with ASI streaming

### Order Information:

<b>AX-61</b>	Modem with ASI streaming
<b>AT-61</b>	Modulator with ASI streaming
<b>AR-61</b>	Demodulator with ASI streaming

### Hardware options:

<b>IF50</b>	additional 50 $\Omega$ IF output and 50 $\Omega$ /75 $\Omega$ switchable IF input
<b>IF75</b>	additional 75 $\Omega$ IF output and 50 $\Omega$ /75 $\Omega$ switchable IF input
<b>EXT</b>	extended operating temperature range of -30°C ... +60°C

Hardware options may only be available for certain device types and are not field-upgradable. Please contact factory with specific requests.

### License based options:

License based options are field-upgradable by a license file.

#### **TXDxxx** transmission data rate limit / applicable to AX-61 and AT-61 devices

TXD10	max 10 Mbps throughput towards satellite
TXD30	max 30 Mbps throughput towards satellite
TXD100	max 100 Mbps throughput towards satellite
TXD160	max 160 Mbps throughput towards satellite
TXDmax	max throughput according to specification

#### **TXSxxx** transmission symbol rate limit / applicable to AX-61 and AT-61 devices

TXS15	max 15 Msps Tx carrier
TXS30	max 30 Msps Tx carrier
TXS45	max 45 Msps Tx carrier
TXS60	max 60 Msps Tx carrier
TXSmax	max Tx carrier according to specification

Either a symbol rate or a data rate based license has to be selected. License model can be changed in field.

#### **RXDxxx** reception data rate limit / applicable to AX-61 and AR-61 devices

RXD10	max 10 Mbps throughput from satellite
RXD30	max 30 Mbps throughput from satellite
RXD100	max 100 Mbps throughput from satellite
RXD160	max 160 Mbps throughput from satellite
RXDmax	max throughput according to specification

#### **RXSxxx** reception symbol rate limit / applicable to AX-61 and AR-61 devices

RXS15	max 15 Msps Rx carrier
RXS30	max 30 Msps Rx carrier
RXS45	max 45 Msps Rx carrier
RXS60	max 60 Msps Rx carrier
RXSmax	max Rx carrier according to specification

Either a symbol rate or a data rate based license has to be selected. License model can be changed in field.

<b>BBO</b>	baseband frame output interface over IP
<b>BBI</b>	baseband frame input interface over IP
<b>TSO</b>	transport stream over IP output
<b>TSI</b>	transport stream over IP input
<b>IQ</b>	IQ raw data output over IP
<b>DAE</b>	data encapsulation for IP network operation with DVB-S2/S2X
<b>DAD</b>	data decapsulation for IP network operation with DVB-S2/S2X

Available licenses are subject to change. Please contact factory for additional features and customized licenses for OEM products.

